

## BRONCE

BUJES DE BRONCE					
NORMA ASTM B-145 C83600 (SAE-40) & ASTM 937-3A C93700 (SAE-64)					
DIMENSION			DIMENSION		
Dametro Exterior	Diametro interior	Kg/pulg	Dametro Exterior	Diametro interior	Kg/pulg
1"	1/2"	0,154	3-3/4"	2"	1,195
1-1/4"	1/2"	0,177		2-1/2"	0,941
	3/4"	0,140	4"	1"	1,757
1-1/2"	3/4"	0,231		2"	1,450
	1"	0,200		2-1/2"	1,218
1-3/4"	1"	0,277		3"	0,900
	1-1/4"	0,231	4-1/2"	3/4"	2,300
2"	3/4"	0,454		1-1/2"	2,100
	1"	0,420		2"	1,950
	1-1/4"	0,338		2-1/2"	1,670
2-1/4"	3/4"	0,581		3"	1,420
	1"	0,523		3-1/4"	1,344
	1-1/4"	0,453		3-1/2"	1,033
	1-1/2"	0,370		3-3/4"	1,026
2-1/2"	3/4"	0,731	5"	2"	2,500
	1"	0,650		2-1/2"	2,250
	1-1/4"	0,560		3"	2,000
	1-1/2"	0,530		3-1/4"	1,801
	1-3/4"	0,435		3-1/2"	1,564
2-3/4"	1"	0,830		4"	1,173
	1-1/4"	0,730	5-1/2"	4"	1,173

### NORMA ASTM B-145 C83600 (SAE-40) & ASTM 937-3A C93700 (SAE-64)

DIMENSION			DIMENSION		
Dametro Exterior	Diametro interior	Kg/pulg	Dametro Exterior	Diametro interior	Kg/pulg
	1-1/2"	0,692	6"	2-1/2"	3,649
	2"	0,461		3"	3,436
3"	1/2"	1,060		3-1/2"	2,932
	3/4"	1,050		4"	2,462
	1"	1,000		5"	1,524
	1-1/2"	0,850	7"	5"	3,000
	2"	0,661		6"	1,596
3-1/4"	1-1/2"	1,000	8"	6"	3,350
	2"	0,800		7"	1,754
	2-1/2"	0,590	9"	6"	5,607
3-1/2"	3/4"	1,300		7"	4,011
	1"	1,325		8"	2,258
	1-1/2"	1,254	10"	7"	6,353
	2"	1,039		8"	4,599
	2-1/2"	0,815		9"	1,319